

EVERLAST™ Eco-Smart™ Wood Finish

Beauty Of A Varnish and Tung Oil—Toughness Of A Polyurethane Very Unique and One Of Its Kind!



Key Product Benefits

- ✓ Interior/Exterior, tough and durable like a poly
- ✓ Beauty of a Varnish and Tung-Oil
- ✓ Eco-Friendly with Pleasant Odor
- ✓ Quick drying, and with enhances productivity features*
- ✓ No plastic like appearance
- ✓ Non-Flammable, Low Combustibility; great for onsite jobs
- ✓ Smooth finish straight from the spray gun
- ✓ No limit on number of coats applied
- ✓ Easy application by spray, brush, roller, or wipe-on
- ✓ Superb Durability with Excellent Chemical Resitance
- ✓ High Solids, High Build; usually requires only 2 coats
- ✓ Sanding between coats not required*
- ✓ Blocks UV rays from damaging stain or wood substrate
- ✓ Excellent mar and abrasion resistance
- ✓ Adheres to any finish for added durability or repair, including UV coatings; nothing like it
- ✓ Superior Performance and Durability to Tung Oil

This **Eco-Smart™**, *pleasant odor*, and quick drying wood finish combines warmth and clarity of a varnish and of tung-oil with the toughness and durability of a polyurethane. Superior product to tung-oil, though—more durable, dries and cures at least 75% faster. Its advanced technology formula makes **EVERLAST™** wood finish suitable for onsite jobs too, as for example finishing or refinishing a bar top on site or restaurant tables. Provides fast and superior protection, color retention and easy repair to all interior and exterior woodwork: kitchen cabinets, doors, trim, paneling, bar tops, table tops, school desks, etc. **EVERLAST™** wood finish is easy to use and repair with excellent resistance to staining, alcohol, water spotting, and most cleaning chemicals. Dries in about two (2) hours (at 75°F and 45% relative humidity), tack free in about 30 minutes, recoat in 3-5 hours*. Its light straw color enhances color of the natural wood grain or stain. It absorbs UV rays into itself, thus protects the wood substrate from UV damage. Resists cracking, flaking or chipping unlike a conversion varnish. Builds fast and is VOC compliant in all 50 states. No need to sand between coats if recoated within 48 hours. Excellent product for topcoating over any finish to enhance durability and water resistance.

The **EVERLAST™** Sealer offers deep sealing of the wood grain for enhanced resistance to water migration, thus damage or lifting. Two coats are recommended on open grain woods.

Apply by spray, brush, roller, paint pad, or wipe on as supplied. Thin for spray application up to 20% with our **EVERLAST™** Reducer. Available in three sheens: Gloss = 92, Semi-Gloss = 75, Satin = 50%.

Not recommended for flooring. Use our **EVERLAST™** GYMCOAT p 16 for superior wear and scuff resistance.

Solids, by wt.:	50%
Solids by vol.:	46%
Viscosity:	20-25 sec. #4 Ford Cup
Coverage: Top Coat.....	500-600 sq. ft. per gallon
Sealer.....	200-300 sq. ft. per gallon
Recoat time @ 75°F, 45% RH:	3 - 5 hours *
Drying time @ 75°F, 45% RH:	Dust free, 30 min.
VOC:	2.29 lbs/gal (275 g/L)

***EVERLAST's** unique properties allow recoating by spray application every ten (10) minutes or so (while tacky), provided ample drying time (usually 24 hours) is given prior to applying the last coat and, next to the last coat is sanded thoroughly with 220-400 no load sandpaper to remove any imperfections.

To enhance drying time, **EVERLAST™** Drier can be added at 2-4 oz per gallon at anytime in the finishing schedule, though avoided in exterior application since ample cure time is required for exterior durability and longevity.

Size	Gloss 92% Sheen	Semi-Gloss 70% Sheen	Satin 50% Sheen	Sealer	Price	EVERLAST REDUCER
1 Qrt	40100	40200	40300	40500	\$12.95	40400 \$10.95
1 Gal	40101	40201	40301	40501	\$29.95	40401 \$14.95
5 Gal	40105	40205	40305	40505	\$99.95	40405 \$59.95



EVERLAST™ Drier		
ED-004	4 oz	\$3.95
ED-008	8 oz	\$7.95
ED-032	Quart	\$21.95

"This is a great multi-purpose wood finish and I also use it over my regular lacquer to enhance its durability"

John Arslanian
Arslanian Furniture Restoration