

GREEN TECHNOLOGY™ GYMCOAT™



This high-performance floor finish contains the most elite and innovative proprietary resins for the most demanding requirements in the coatings industry. It is highly recommended for residential, commercial and sport flooring that demand green technology, or where sensitivity to chemicals or odors is essential. Makes floor finishing and refinishing safe and easy, and furthermore the finish is easily repairable down the line. Non-yellowing and quick drying. Recommended for interior use only.

Apply by brush, roller, applicator or spray. *For interior use only. This is a self sealing finish.* However, for color enhancement to the wood grain, use a single coat of **EVERLAST™ Sealer** (page 4) under this finish.

Excellent replacement product for tung-oil finish when used in conjunction with the **EVERLAST™ Sealer**.

Available in gloss, satin and dull-satin. Coverage, 400 SF/gal

Key Features

- ✓ Green Technology™ Formula
- ✓ Quick Drying and Non-Yellowing
- ✓ Outstanding Clarity and Depth
- ✓ Outstanding Warmth and Grain Definition
- ✓ Superb Durability for Use In High Traffic Areas
- ✓ Excellent Flow and Leveling
- ✓ No Catalyst/Pot Life Problem or Restrictions
- ✓ Recoatable any time - **100% burn-in**

Solids, by wt.:	35%
Solids by vol.:	33%
Viscosity:	25-30 sec. #4 Ford Cup
Coverage:	400 sq. ft. per gallon
Recoat time @ 75°F, 45% RH:	2 hours
Drying time @ 75°F, 45% RH:	Dust free, 15 min.
VOC:	0.5 lbs/gal (60 g/L)

IMPORTANT: Do not use tack cloth between coats. It can cause improper cure, crazing, lifting or peeling.

SIZE	GLOSS	SATIN	DULL SATIN	WT.	PRICE
GAL	70201	70301	70401	10#	\$ 69.95
5 GAL	70205	70305	70405	46#	\$279.95
55 GAL	70255	70355	70455	475#	Call for pricing

EVERLAST™ GYMCOAT™ Eco-Smart™



This high performance, *pleasant odor*, quick drying, and *non-flammable* finish fullfills the most demanding requirements in the wood floor coatings industry. **EVERLAST™ GYMCOAT** is elastic, waterproof and able to withstand the wear and abrasion of high *foot* traffic. By far a more effective and durable finish than Tung-oil from the aspect of cure time, mar and abrasion resistance, drying time, and odor yet, provides equal richness and beauty.

Provides a rock hard finish in 24 hours; Tung-oil on the other hand takes thirty (30) days to cure, and Tung-oil doesn't even approach the hardness and mar resistance of the **EVERLAST™ GYMCOAT**.

It is ecologically friendly in terms of low VOC and pleasant odor. Dries in about two (2) hours (at 75° F and 45% relative humidity), tack free in about 30 minutes, recoat in 6 hours. Its light straw color enhances the color of the wood grain. It absorbs UV rays into itself, thus protects the wood substrate and stain from UV damage. Resists flaking and chipping and is easy to repair at anytime. Builds fast and usually requires only two coats, plus sealer.

The sealer offers deep sealing of the wood grain thus enhanced durability. The sealer is odorless.

EVERLAST™ GYMCOAT is also an excellent product for use on outside decking, and generally a couple of coats of the sealer will do just fine, provided low film build is desired.

Apply by brush, roller, paint pad, spray, or lambswool applicator.

Key Product Benefits

- ✓ Interior/Exterior
- ✓ Pleasant Odor
- ✓ Non-Flammable
- ✓ Superb Durability and Excellent Scuff Restance
- ✓ No Limit On Number Of Coats Applied
- ✓ Easy Application by Spray Brush, Roller, Paint Pad, or Wipe-On
- ✓ High Build, Usually Requires Only 2 Coats
- ✓ Quick Drying, Reduces Time Between Coats
- ✓ Sanding Between Coats Not Required
- ✓ Blocks UV Rays From Damaging Stain Or Substrate
- ✓ No Plastic Like Appearance
- ✓ Excellent Abrasion Resistance
- ✓ Adheres To Any Finish For Added Durability or Repair, including UV Coatings
- ✓ Superior Performance and Durability to Tung Oil

Available in Gloss (94% sheen), Semi-Gloss (70%) and Satin (50%)

Solids, by wt.:	50%
Solids by vol.:	46%
Viscosity:	20-25 sec. #4 Ford Cup
Coverage:	Top Coat..... 500-600 sq. ft. per gallon
	Sealer..... 200-300 sq. ft. per gallon
Recoat time @ 75°F, 45% RH:	3 - 4 hours *
Drying time @ 75°F, 45% RH:	Dust free, 30 min.
VOC:	2.29 lbs/gal (275 g/L)

For stain requirements, our Wiping Wood Stain is highly recommended for best results. See page 10.



Size	Gloss 92% Sheen	Semi-Gloss 75% Sheen	Satin 50% Sheen	Price	Sealer	Price
1 Gal	44101	44201	44301	\$69.95	40501	\$29.95
5 Gal	44105	44205	44305	\$279.95	40505	\$99.95