

**HYGIENIC PRACTICES:** wash hands thoroughly after handling. Remove and wash contaminated clothing immediately.

**PROTECTIVE GLOVES:** Neoprene rubber or similar type.

**EYE PROTECTION:** splash-proof goggles.

**OTHER PROTECTIVE EQUIPMENT:** solvent resistant aprons and armguards to avoid soiling of work clothes.

**SECTION IX – SPECIALPRECAUTIONS**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Keep containers closed when not in use. Store away from ignition sources. Store and use in well ventilated areas. Keep out of the reach of children.

**OTHER PRECAUTIONS:** Empty container may retain product residues (vapor or liquid). All precautions must be observed. All equipment should be grounded prior to use with this product

Disposal of containers should be in accordance with applicable laws and regulations. "EMPTY" containers should not be given to individuals. Serious accidents have resulted from the misuse of "Empties" containers (drums, pails, etc).

**DISCLAIMER:**

HOOD FINISHING PRODUCTS, INC. believes that the data contained herein are accurate and derived from qualified sources – and the data are not to be taken as a warranty or representation for which HOOD FINISHING PRODUCTS assumes legal responsibility. The data offered is solely for your consideration, investigation and verification. Any use of this data and information must be determined by the user to be in accordance with applicable local, State and Federal regulations.

Questions? Call: 1-800-229-0934 Fax: 732-828-7325



**MATERIAL SAFETY DATA SHEET**

HOOD FINISHING PRODUCTS, Inc.  
PO Box 97  
Somerset, NJ 08875-0097

Health Emergency..... 732-828-7850  
Spill Emergency..... 732-828-7850  
Other Information.....800-424-9300  
CHEMTREC..... 800-424-9300

**DATE:** 12/1/08

**SECTION I - PRODUCT IDENTIFICATION**

**PRODUCT NAME:** LACQUER FLATTING AGENT  
**PRODUCT NUMBERS:** 91801  
**PRODUCT CLASS:** LACQUER ADDITIVE  
**PRODUCT USE:** WOOD COATING  
**DOT PROPER SHIPPING NAME:** PAINT RELATED MATERIAL  
**DOT HAZARD CLASSIFICATION:** FLAMMABLE LIQUID **DOT ID #:** UN-1263

	<u>HMIS RATING</u>	<u>SCALE</u>
HEALTH:	2	4=EXTREME
FLAMMABILITY:	3	3=HIGH
REACTIVITY:	1	2=MODERATE
PERSONAL PROTECTION:	H	1=SLIGHT
		0=INSIGNIFICANT

**SECTION II - HAZARDOUS INGREDIENTS**

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>WEIGHT PERCENT</u>	<u>OSHA OCCUPATIONAL EXPOSURE LIMITS</u>	
			<u>PEL (PPM)</u>	<u>STEL (PPM)</u>
Toluene*	108-83-3	35.0	100	150
Amorphous Silica	7631-86-9	21.0	6 mg/m <sup>3</sup>	
Isopropanol	67-63-0	10-15	400	500
Methanol*	67-56-1	10.0	200	250
Butyl Acetate*	123-86-4	1-10	150	200
Acetone*	67-64-1	7.0	750	1000
Methyl Ethyl Ketone*	78-93-3	7.0	200	300
2-Butoxy Ethanol*	111-76-2	2.0	25	50

N/A = Not Applicable      NA = Not Available      NE = Not Established  
Items indicated by \* are subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1980 and of 40CFR 372.

## SECTION III - PHYSICAL DATA

APPEARANCE:	Amber Color
STATE:	Viscous Liquid
ODOR CHARACTERISTICS:	Strong Solvent Odor
pH	NA
VISCOSITY (#4Ford Cup):	N/A
SPECIFIC GRAVITY:	0.86
VAPOR DENSITY:	>1
VAPOR PRESSURE:	NE
MELTING POINT:	N/A
BOILING POINT:	133-724°F
SOLUBILITY IN WATER:	Slight
PERCENT VOLATILES BY VOLUME:	79.0%
EVAPORATION RATE:	<1
VOC, lbs/gal (g/L)	5.63 (676)

## SECTION IV- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (TCC): 31°F LEL: NE

## EXTINGUISHING MEDIA:

Foam CO<sub>2</sub>, Dry Chemical  
DO NOT USE WATER TO EXTINGUISH

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** During emergency conditions, over exposure to decomposition products (see action VI-Reactivity Data) may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention. Keep containers tightly closed. Isolate from heat, spark and open flame. Closed containers may explode when exposed to extreme heat.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup and possible explosion when exposed to extreme heat. Full protective equipment, including self contained breathing apparatus is needed to protect fire fighters from exposure to coating's hazardous ingredients and hazardous combustion products.

## SECTION V- HEALTH HAZARD DATA

**EFFECTS OF OVEREXPOSURE:** Harmful if inhaled. May be fatal or cause blindness if swallowed. Irritating to eyes, skin and respiratory tract.

**OTHER SYMPTOMS MAY INCLUDE:** dizziness, nausea, narcosis, headache.

**MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:** pulmonary conditions.

**CHRONIC HEALTH HAZARD:** Lung damage, cardiac abnormalities, central nervous system damage.

**REPEATED OVEREXPOSURE TO THIS PRODUCT MAY CAUSE:** central nervous system damage, kidney damage, liver abnormalities, lung damage, cardiac abnormalities, blood effects, eye damage.  
**NOTICE:** reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

**EMERGENCY AND FIRST AID PROCEDURE:** **EYE CONTACT:** flush immediately with plenty of water for at least 15 minutes and get medical attention. **SKIN:** wash thoroughly with soap and water. **INHALATION:** remove to fresh air. **INGESTION:** do not induce vomiting. Get medical attention **IMMEDIATELY**

## SECTION VI- REACTIVITY DATA

**THIS PRODUCT IS STABLE UNDER NON-EMERGENCY CONDITIONS.**

**HAZARDOUS POLYMERIZATION WILL NOT OCCUR.**

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon.

**CONDITIONS TO AVOID:** heat, open flame, sparks

**MATERIAL TO AVOID:** oxidizers, strong alkali, strong acids

## SECTION VII - SPILL OR LEAK PROCEDURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** ventilate area of spill before attempting clean-up. Cover spilled remover with absorbent material, VERMICULIATE or similar. Do not use Sawdust. Place wet absorbent into metal containers (covered) and place outdoors. Spark proof tools (shovels/scoops) should be used.

**WASTE DISPOSAL METHOD:** Dispose of remover waste in accordance with all local state, and federal regulations.

## SECTION VIII- SAFE HANDLING AND USE INFORMATION

**RESPIRATORY PROTECTION:** REQUIRED IF EXPOSURE LEVEL ABOVE OSHA PEL.

**VENTILATION:** mechanical ventilation sufficient to keep exposure below federal, state, and local regulations.