

## GREEN TECHNOLOGY GYMCOAT

**HYGIENIC PRACTICES:** wash hands thoroughly after handling.

**PROTECTIVE GLOVES:** Latex or nitrile gloves.

**EYE PROTECTION:** splash-proof goggles.

**OTHER PROTECTIVE EQUIPMENT:** None

### SECTION IX – SPECIAL PRECAUTIONS

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** None.

Keep out of the reach of children.

**OTHER PRECAUTIONS:** None

Disposal of containers should be in accordance with applicable laws and regulations. "EMPTY" containers should not be given to individuals. Serious accidents have resulted from the misuse of "Empties" containers (drums, pails, etc).

#### **DISCLAIMER:**

HOOD FINISHING PRODUCTS, INC. believes that the data contained herein are accurate and derived from qualified sources – and the data are not to be taken as a warranty or representation for which HOOD FINISHING PRODUCTS assumes legal responsibility. The data offered is solely for your consideration, investigation and verification. Any use of this data and information must be determined by the user to be in accordance with applicable local, State and Federal regulations.

Questions? Call: 1-800-229-0934 Fax: 732-828-7325



## MATERIAL SAFETY DATA SHEET

HOOD FINISHING PRODUCTS, Inc.  
PO Box 97  
Somerset, NJ 088875-0097

Health Emergency..... 732-828-7850  
Spill Emergency..... 732-828-7850  
Other Information.....800-424-9300  
CHEMTREC..... 800-424-9300

**DATE:** 12/1/08

### SECTION I - PRODUCT IDENTIFICATION

**PRODUCT NAME:** GREEN TECHNOLOGY GYMCOAT  
**PRODUCT NUMBERS:** 702XX , 703XX, 704XX  
**PRODUCT CLASS:** FINISH  
**PRODUCT USE:** WOOD COATING  
**DOT PROPER SHIPPING NAME:** PAINT RELATED MATERIAL  
**DOT HAZARD CLASSIFICATION:** N/A DOT ID N/A

HMIS RATING		SCALE
HEALTH:	1	4=EXTREME
FLAMMABILITY:	0	3=HIGH
REACTIVITY:	0	2=MODERATE
PERSONAL PROTECTION:	C	1=SLIGHT
		0=INSIGNIFICANT

### SECTION II - HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>WEIGHT PERCENT</u>	<u>OSHA OCCUPATIONAL EXPOSURE LIMITS</u>	
			<u>PEL (PPM)</u>	<u>STEL (PPM)</u>
Dipropylene Glycol Methyl Ether	34590-94-8	3-5	100	150

N/A = Not Applicable      NA = Not Available      NE = Not Established  
Items indicated by \* are subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1980 and of 40CFR 372.

# MATERIAL SAFETY SHEET GREEN TECHNOLOGY GYMCOAT

## SECTION III - PHYSICAL DATA

APPEARANCE: Milky off white  
STATE: Liquid  
ODOR CHARACTERISTICS: Slight Ammonia Odor  
pH: 8.0-8.5  
VISCOSITY (#4Ford Cup): 25-30 sec  
SPECIFIC GRAVITY: 1.037  
VAPOR DENSITY: >1  
VAPOR PRESSURE: NE  
MELTING POINT: N/A  
BOILING POINT: Not Established  
SOLUBILITY IN WATER: Complete  
PERCENT VOLATILES BY VOLUME: N/A  
EVAPORATION RATE: >1  
VOC, lbs/gal (g/L): 0.5 (60 g/L)

## SECTION IV- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (TCC): None LEL: N/A

EXTINGUISHING MEDIA: Not applicable

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SPECIAL FIREFIGHTING PROCEDURES: None

## SECTION V- HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: None

OTHER SYMPTOMS MAY INCLUDE: None known

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: None.

CHRONIC HEALTH HAZARD: None.

REPEATED OVEREXPOSURE TO THIS PRODUCT MAY CAUSE: None

EMERGENCY AND FIRST AID PROCEDURE: EYE CONTACT: flush immediately with plenty of water for at least 15 minutes and get medical attention. SKIN: wash thoroughly with soap and water.  
INHALATION: None

## SECTION VI- REACTIVITY DATA

THIS PRODUCT IS STABLE UNDER NON-EMERGENCY CONDITIONS.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, hydrocarbons fumes.

CONDITIONS TO AVOID: extreme heat, open flame, sparks

MATERIAL TO AVOID: None known

## SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: clean up all spills and dispose in accordance with local regulations, if applicable.

WASTE DISPOSAL METHOD: Dispose of remover waste in accordance with all local state, and federal regulations.

## SECTION VIII- SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: REQUIRED IF EXPOSURE LEVEL ABOVE OSHA PEL.  
VENTILATION: OSHA approved Vapor respirator.