

EVERLAST™ Eco Friendly Clear Varnish/Polyurethane



Interior/Exterior Quick Drying

Key Product Benefits

- ✓ Interior/Exterior
- ✓ Pleasant Odor
- ✓ Non-Flammable
- ✓ Superb Durability with Excellent Chemical Resistance
- ✓ No Limit On Number Of Coats
- ✓ Easy Application by Spray Brush, Roller, Paint Pad, or Wipe-On
- ✓ High Build, Usually Requires Only 2 Coats
- ✓ Quick Drying, Reduces Time Between Coats
- ✓ Sanding Between Coats Not Required
- ✓ Blocks UV Rays From Damaging Stain Or Substrate
- ✓ No Plastic Like Appearance
- ✓ Excellent Abrasion Resistance
- ✓ Adheres To Any Finish For Added Durability or Repair, Including UV Coatings
- ✓ Superior Performance and Durability to Tung Oil

This *pleasant odor*, quick drying, and *non-flammable* oil-modified finish combines warmth and clarity of a varnish and tung-oil with the toughness and durability of a polyurethane. Yet, much superior product than tung-oil finish in cure time and durability. Its advanced technology and unique attributes makes **EVERLAST™** suitable for onsite jobs. Provides fast and superior protection, color retention and easy repair to all interior and exterior woodwork: kitchen cabinets, doors, trim, paneling, bar tops, table tops, school desks, etc. **EVERLAST™** is easy to use and has excellent resistance to abrasion, foot traffic, stains, alcohol, water spotting, acids and alkali, etc. Dries within two (2) hours (at 75° F and 45% relative humidity), tack free in about 30 minutes, recoat in 4-6 hours*. Its light straw color enhances color of the wood grain. It absorbs UV rays into itself, thus protects the wood substrate from UV damage. Resists flaking and chipping. Supplied at 50% solids, thus builds fast and is VOC compliant in all 50 states. No need to sand between coats if recoated within 24 hours.

The sealer offers deep sealing of the wood grain for enhanced resistance to water migration, thus damage or lifting. It's odorless.

Apply by spray, brush, roller, paint pad, or wipe on. Should be thinned only for spray application up to 25% with our **EVERLAST™ Reducer**.

To enhance drying time, **EVERLAST™ Drier** can be added at 2 oz per gallon at any time in the schedule of finishing.

Available in three sheens: **Gloss = 92, Semi-Gloss = 70, Satin = 50%.**



Solids, by wt.:	50%
Solids by vol.:	46%
Viscosity:	20-25 sec. #4 Ford Cup
Coverage:	Top Coat..... 500-600 sq. ft. per gallon
	Sealer..... 200-300 sq. ft. per gallon
Recoat time @ 75°F, 45% RH:	3 - 4 hours *
Drying time @ 75°F, 45% RH:	Dust free, 30 min.
VOC:	2.29 lbs/gal (275 g/L)

***EVERLAST's** unique properties permit recoating by spray application every ten (10) minutes or so (while still tacky), provided ample drying time (usually 24 hours) is given prior to applying the last coat and, next to the last coat is sanded thoroughly with 220-400 no load sandpaper to remove any imperfection.

Size	Gloss 92% Sheen	Semi-Gloss 70% Sheen	Satin 50% Sheen	Sealer	Price	EVERLAST REDUCER	
1 Qrt	40100	40200	40300	40500	\$12.25	40400	\$10.95
1 Gal	40101	40201	40301	40501	\$28.95	40401	\$14.95
5 Gal	40105	40205	40305	40505	\$98.95	40405	\$59.95

EVERLAST™ Drier

ED-004	4 oz	\$3.95
ED-008	8 oz	\$7.95
ED-032	Quart	\$19.95

Recommended addition, 2-4 oz per gallon