

# MAGNA-SHIELD® OPTIMIZED

## There Is No Better, Faster Or Easier Way To Finish Interior Furniture, Cabinets and More...*Like No Other Wood Lacquer In Its Class!*

Magna-Shield® means no second-guessing, no crossed fingers, and no concessions to performance, quality, durability or value. It's like no other wood lacquer on the market.

Your choice in the best wood lacquer is one decision *you* and *your* customers focus on day after day, week after week. That's why it is so important to insist upon the one brand of pre-catalyzed lacquer that delivers everything on your requirement check list — from excellent durability and clarity to user friendly features. With Magna-Shield®, you don't have to settle!

Equally important, its enhanced properties **bridges the gap between conventional lacquer and conversion varnish** in terms of hardness and durability, but, without chipping, cracking or recoatability issues encountered with conversion varnishes or, lack of durability and resistance of a typical lacquer. Furthermore, under most application conditions, **Magna-Shield®** needs no thinning or addition of a retarder to enhance its performance properties.

### Magna-Shield's® Unique and Optimized Features

- ✓ Self-Sealing\* and Quick Drying
- ✓ Tough and Durable with Excellent Chemical Resistance
- ✓ High Build and Non-Yellowing
- ✓ Recoat Anytime, and No Limit On Number Of Coats
- ✓ VOC Compliant
- ✓ Superb Depth and Clarity
- ✓ Non-Blushing (up to 96% Relative Humidity)
- ✓ Ready To Spray with Excellent Flow and Leveling
- ✓ No Catalyst/Pot Life Problem or Restrictions
- ✓ No Thinner nor Retarder Needed in Most Applications
- ✓ Sanding Between Coats Not A Must
- ✓ Perfect Finish Straight From The Spray Gun
- ✓ Meets KCMA Standards For Use On Kitchen Cabinets
- ✓ Can now be post catalyzed with Magna-Shield Catalyst on the last coat for faster cure and print resistance *approaching that of a conversion varnish*



**Transforms Wood Finishing  
Into The  
Extraordinary**

Solids, by wt.:	40%
Solids by vol.:	35%
Viscosity:	20-25 sec. #4 Ford Cup
Coverage:	600 sq. ft. per gallon
Recoat time @ 75°F, 45% RH:	60 minutes
Drying time @ 75°F, 45% RH:	Dust free, 5-10 min.
VOC:	4.5 lbs/gal (540 g/L)

\*Magna-Shield® can be applied over a sanding sealer or a vinyl sealer, if so desired. However, sanding sealer coats should be up to two (2) only then sanded down and up to two (2) coats for vinyl sealer which do not have to be sanded off, only sanded.

### Magna-Shield® Clears\*\*

Size	High Gloss 90% Sheen	Gloss 75% Sheen	Satin 45% Sheen	"Dull" Satin 25% Sheen	Matte 15% Sheen	Price
1 Gal	MS9001	MS9101	MS9201	MS9301	MS9401	\$28.95
5 Gal	MS9005	MS9105	MS9205	MS9305	MS9405	\$129.00

\*\* Water-clear and non-yellowing. Use over any stain or type of wood, will not discolor

### Magna-Shield® Catalyst

MS-CAT-004	4 oz	\$3.95
MS-CAT-008	8 oz	\$7.95
MS-CAT-032	Quart	\$19.95

Recommended amount 2 oz per gallon

### Magna-Shield® Pigmented

Size	White Gloss	White Satin	White Primer	Black Gloss	Black Satin	Black Primer	Price
1 Gal	MS6101	MS6201	MS6301	MS6601	MS6701	MS6801	\$ 29.95
5 Gal	MS6105	MS6205	MS6305	MS6605	MS6705	MS6805	\$134.00

**IMPORTANT: Do not use tack cloth between coats. It can cause crazing.**